


EFFICIENCY WITH STRENGTH

MACHETE[®]2
SECOND GENERATION

A yellow boom mower is shown in operation on a grassy field. The mower's boom is extended upwards and to the right, cutting through tall grass. The background is a dark, shadowed area, possibly a wooded area or a deep shadow from a building. The mower has "MACHETE 2" and "ALAMO INDUSTRIAL" printed on it.

Unruly vegetation is no match for the power of the Machete[®]2. With 215° head rotation and 120° boom swing, this mower makes a clean sweep of the competition. The ability to cut through material up to five inches in diameter makes it ideal for parks, airports, roadside, and right-of-way clearing.

Machete[®]2

Boom Mower

Machete[®]2



Safely Stored

A two-piece boom rest cradles the boom securely in place while in transport and storage.

Convenient Control

A joystick control is standard equipment and keeps all boom functions at your fingertips.

Versatility You Need

An improved four-bar design allows for 215° head rotation to maneuver into tight spaces. An optional head swivel reduces overall transport width.

Heavy Duty Cutting

Cut up to 5" diameter material with the rotary cutting head available in 50" and 60" widths. Choose from a variety of heads to fit your application from grass to limbs and brush.

Built with Strength

The boom is constructed of a two-piece design and made completely of heavy duty alloy steel for longevity. It features 2" pins with greaseable, hardened steel bushings.

Optimal Visibility

A high frame is featured to improve operator visibility.

Designed for Longevity

The heavy duty cast turning arm features a 2 1/2" diameter king pin which swings up to 120°. All pivot points feature greaseable, hardened steel bushings to insure maximum bearing life.

Efficient Hydraulics

The unit features a closed loop piston pump for the motor circuit, while the control circuit features a load sensing piston pump and electro-hydraulic control valve. The self contained system allows the Machete[®]2 hydraulic system to operate independent of the tractor's system.

This information is intended to be of a general nature only; specifications are subject to change without notice as we continue to improve our products.

© 2013 Alamo Group Inc. Registered trademarks identified are property of Alamo Group Inc.

MEMBER OF THE
ALAMO GROUP
ALWAYS ON THE CUTTING EDGE.

Additional Specifications

- Tractor Requirements:
- 8,500 lb. minimum shipping weight with an 90" minimum wheelbase
 - Engine: 90 hp minimum
 - Minimum 18" ground clearance
 - 25 ft models require 4WD option

Warranty: One year parts and labor. Nongovernmental users are subject to a modified policy. Only genuine Alamo Industrial[®] parts may be used for warranty replacement.



Always purchase genuine OEM parts.
1-800-882-5762

ALAMO
INDUSTRIAL

BUILT SHARPER[®]

1502 East Walnut St. • Seguin, Texas 78155

1-800-882-5762

www.alamo-industrial.com